

Improved Thermophotovoltaic Energy Conversion with 3-D Tungsten Photonic Crystal

C. Murray, J. Fleming, R. Koudelka, D. L. Chubb and I. El-Kady
Sandia National Laboratories, PO Box 5800, Albuquerque, NM, USA

Recent advances in thermophotovoltaic (TPV) energy conversion efficiencies to greater than 20% has increased interest in investigating the use of TPV in a wider spectrum of applications. One of the issues associated with using TPV is the high hot-side temperatures ($> 1000\text{K}$) necessary to obtain conversion efficiencies greater than 20%. The elevated temperature limits the available materials that can be used as the hot-side emitter to either ceramics or refractory alloys which emit photons with a Planckian distribution. For semiconductor materials of interest for TPV energy conversion the ratio of convertible light to nonconvertible light is 25% for greybody emitters. Therefore, in order to increase the conversion efficiency, very complex cold-side front surface filter technology is utilized.

In order to relax the requirements imposed on the front surface filter, 3-D tungsten photonic crystals (PC) are being investigated for hot-side emitters in TPV energy conversion. The PC increases the emission in the convertible wavelength range (over bulk tungsten) and suppresses the emission in the non-convertible wavelength range, which results in a greater than 10% improvement in conversion efficiency. Recent efforts utilizing tungsten PC for mWe power conversion will be reported.

This work was supported by DARPA under the Radioisotope Micropower Sources (RIMS) program. Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy's National Nuclear Security Administration under Contract DE-AC04-94AL85000.